## LCDM5VGAM

### TECHNICAL SPECIFICATIONS

5" Video/VGA Input Metal Housed Monitor. Ideal as a **CRT Monitor Replacement. Includes Special** Horizontal & Vertical Adjustment Firmware, as well as a Video Zoom function.



# SLACK WIRE: Connect to Ground RED WIRE: DC Input (+12V) WHITE RCA JACK: Video input #2

\*Specifications subject to change without notice.

Miller Technologies

www.millertech.com

#### **SPECIFICATIONS\***

DISPLAY:

NTSC/PAL/VGA

5" Color TFT LCD

INPUT SIGNAL: RESOLUTION:

640 x 480

BACK LIGHT:

LED

BACKLIGHT LIFE:

15.000 Hrs.

**BRIGHTNESS RATING:** 

250 NIT TYP. 70°/70°/50°/70°

VIEWING ANGLE (L/R/T/B):

POWER REQUIREMENTS:

12VDC @ 300mA

**VIDEO INPUT LEVEL: DIMENSIONS (WxHxD):** 

5 3/4" X 4 5/16" X 1"

1.0 V p-p (positive) 75 Ohm

MOUNTING:

SLIDE MOUNT

**OPERATING TEMPERATURE:** 

-10°~+60°C (14°~140°F)

STORAGE TEMPERATURE:

-10°~+60°C (14°~140°F)

#### **FEATURES**

- IR Remote (OSD)
- **Composite Video Inputs**
- **Rear Slide Mount**
- VGA Computer Input
- Tilt Stand/Mount Included



Pho: (910) 328-2829 Fax: (910) 328-5494

Email: info@millertech.com

**Miller Technologies** 109 Fairytale Lane Surf City, NC 28445