

# LCDP15TS

TOUCH SCREEN MONITOR

# LCDP15TSR

MONITOR WITH CARD READER

## TECHNICAL SPECIFICATIONS

15" TOUCH SCREEN  
MONITOR WITH OPTIONAL  
MAGNETIC STRIPE CARD  
READER



### FEATURES

- USB TOUCH SCREEN
- COUNTERTOP STAND
- WIDE VIEWING ANGLE
- OPTIONAL 3-TRACK MAG CARD READER
- OSD

#### LANGUAGE SUPPORT:

ENGLISH, GERMAN, FRENCH, SPANISH, RUSSIAN, and More...

### MSR CARD READER

<b>COLOR:</b>	Black
<b>USB CABLE LENGTH:</b>	150cm
<b>OPERATING LOCUS:</b>	Indoor
<b>CURRENT:</b>	<45mA
<b>READ TYPE:</b>	1/2/3 Track, Manual Swipe
<b>INTERFACE:</b>	USB
<b>STANDARDS:</b>	ISO 7811
<b>RESPONSE:</b>	LED
<b>FEED:</b>	10-150 mc/sec Card Feed
<b>DIMENSIONS (mm):</b>	90(D) x 27(W) x 28(H)
<b>POWER SUPPLY:</b>	5VDC (supplied by host)
<b>RATED:</b>	800,000 Passes
<b>APPLICATIONS:</b>	POS, Security Contrl, CAT
<b>GROSS WEIGHT:</b>	0.2 kg
<b>OPERATING TEMP:</b>	0°C~60°C
<b>STORAGE TEMP:</b>	-20°C~80°C
<b>OPERATING HUMIDITY:</b>	10%~90%

### SPECIFICATIONS

<b>DISPLAY:</b>	15" Color TFT LCD (4:3)
<b>INPUT SIGNAL:</b>	VGA
<b>DOT FORMAT:</b>	1024 x 768
<b>BACK LIGHT:</b>	LED
<b>BRIGHTNESS RATING:</b>	500 NIT
<b>VIEWING ANGLE (L/R/T/B):</b>	80°/80°/80°/80°
<b>POWER REQUIREMENTS:</b>	110~250VAC 50/60 HZ
<b>INPUT:</b>	15-PIN DSUB (VGA)
<b>DIMENSIONS:</b>	396 X 115 X 378MM
<b>OPERATING TEMPERATURE:</b>	-10°C ~ 60°C (+14°F ~ +140°F)
<b>STORAGE TEMPERATURE:</b>	-20°C ~ +70°C (-4°F ~ +158°F)
<b>TOUCH SCREEN:</b>	4-WIRE RESISTIVE
<b>TOUCH SCREEN LIFE:</b>	>50 MILLION
<b>WEIGHT:</b>	NW: 3.85KG, GW: 4.8KG

\*Specifications subject to change without notice.

**Miller Technologies**  
109 Fairytale Lane  
Surf City, NC 28445

**Miller  
Technologies**

**Pho: (910) 328-2829**  
**Fax: (910) 328-5494**  
**Email: info@millertech.com**

[www.millertech.com](http://www.millertech.com)