

LCDP5LA

TECHNICAL SPECIFICATIONS

5" NTSC/PAL Video Input LCD MONITOR with Stand and Surface/Flush Mount Adapter



FEATURES

- 5" TFT LCD
- NTSC/PAL VIDEO INPUT
- OSD (ON SCREEN DISPLAY)
- NTSC/PAL AUTO SWITCHING
- TILT STAND
- SURFACE/FLUSH MOUNT ADAPTER

SPECIFICATIONS

DISPLAY:	5" Color TFT LCD
INPUT SIGNAL:	NTSC/PAL
RESOLUTION:	960 X 234
BRIGHTNESS RATING:	250 NIT TYP.
VIEWING ANGLE (L/R/T/B):	70°/70°/50°/70°
POWER REQUIREMENTS:	12VDC @ 300 mA
VIDEO INPUT LEVEL:	1.0 V p-p (positive) 75 Ohm
DIMENSIONS (HxWxD):	4 1/4" x 5 5/8" x 1 3/8" (10.8cm x 14.4cm x 3cm)
OPERATING TEMPERATURE:	0° ~ 60°C (32° ~ 140°F)
STORAGE TEMPERATURE:	-20° ~ 80°C (-4° ~ 176°F)

*Specifications subject to change without notice.

Miller Technologies
109 Fairytale Lane
Surf City, NC 28445

Miller
Technologies

www.millertech.com

Pho: (910) 328-2829
Fax: (910) 328-5494
Email: info@millertech.com