

RainDrop™ Industrial LCD monitors

RainDrop™ 6.4", 10.4", 12.1" 15.0" LCD Monitors



The innovative line of waterproof RainDrop™ NEMA sealed flat panel monitors can be wall mounted, arm mounted, desktop mounted. RainDrop™ sealed LCD monitors offer maximum flexibility with various screen sizes to meet most flat panel monitor display applications. Sizes include 6.4", 10.4", 12.1" and 15.0" LCDs.

Standard configurations include a protective thick Plexiglas for LCD screen protection.

RainDrop™ monitors can be ordered with an optional resistive touch screen.

Brightness and contrast controls are behind a sealed removable plate, securing the buttons from accidental resetting.

Each RainDrop™ touch LCD monitor enclosure is manufactured with rugged ABS plastic and adheres to NEMA 4X IP67 standards.

RainDrop™ touch screen displays are ideal for dust or waterproof environments, such as foundries, steel plants, food processors, hospitals and laboratories. RainDrop™ monitors are perfect for industrial touch screen applications.

Features at a Glance

- Rugged ABS construction adheres to NEMA 4X IP67 standards
- Bright 6.4", 10.4", 12.1" and 15.0" TFT LCD screen sizes
- Completely dust proof and water proof
- Auto resizing of screen for various resolution settings
- Brightness and Contrast controls are sealed behind a removable panel
- Protective Plexiglas over front of LCD screen
- Optional Resistive Touch Screen available on all models
- Optional stainless steel wall mount bracket with VESA hole pattern
- Optional stainless steel tilt desk stand (slant only for 6.4")
- Ideal for foundries, steel plants, food processing, mining, hospitals and laboratories
- One Year Warranty
- Made in USA

TECHNICAL SPECIFICATIONS

RainDrop™ Sealed Industrial LCD Monitors

Enclosure:	Sealed Rugged ABS Plastic, adheres to NEMA 4X, IP67 standards		
Dimensions:	RainDrop™ 6.4":	7.860"(H) x 9.436"(W) x 2.094"(D)	
	RainDrop™ 10.4":	10.445"(H) x 12.564"(W) x 2.094"(D)	
	RainDrop™ 12.1":	12.0"(H) x 13.875"(W) x 2.750"(D)	
	RainDrop™ 15.0":	13.940"(H) x 16.375"(W) x 2.745"(D)	
Weight:	RainDrop™ 6.4":	3.0 lbs.	
	RainDrop™ 10.4":	5.0 lbs.	
	RainDrop™ 12.1":	9.0 lbs.	
	RainDrop™ 15.0":	12.0 lbs.	
Display Type:	Color TFT Active Matrix LCD		
Resolution: (Call for higher resolutions)	RainDrop™ 6.4":	640 x 480	180 nit
	RainDrop™ 10.4":	640 x 480	300 nit
	RainDrop™ 12.1":	800 x 600	280 nit
	RainDrop™ 15.0":	1024 x 768	250 nit
Optional Touch Screen:	Resistive		
Non-Operating Temperature:	-20°C ~ 60°C		
Operating Temperature:	0°C ~ 50°C		
Operating Shock:	10g, 11ms, 1/2 sine		
Operating Vibration:	0.41g, 3-500 Hz		
Video Interface:	Sealed DB15(F) VGA connector (standard). Optional special order composite video (NTSC, PAL & VGA) interface		
Touch Screen Interface:	DB9(M) serial connector (serial touch screen controller)		
Cable:	Each monitor comes with a 6 foot Male-to-Male VGA DB15 extender cable. Optional sealed connector available.		
Power:	External power supply with cable.		
Accessories:	Sealed Barcode Badge Reader, Magnetic Stripe Reader, CCD or Laser handheld scanner, and more. Call for details.		
Mounting Hardware:	Optional Pendant mount, Wall Bracket with VESA hole pattern or Tilt Desk Stand (Slant only for RainDrop™ 6.4").		
Power:	115/230 VAC		

Represented By:
Miller Technologies
109 Fairytale Ln
Surf City, NC 28445

Made in the USA
Specifications are subject to change without notice.

PHO: 910-328-2829
FAX: 910-328-5494
EMAIL: sales@millertech.com
WEB SITE: www.millertech.com